

3300XSIP Legendary Reliability

Avoids Hand Contact With Push Paddle Taps
& SIPneo3 Automatic Sanitisation

- Manual taps and lack of any PCB's or solenoids makes for easy maintenance
- Built on the same platform, and uses many of the same parts as the well known, ArcticChill88/98 and ArcticStar55
- The 3300X fits our overflow kit, our cowlings and mains drainage kit with or without pump
- SIPneo3 24/7 self sanitising system installed



3300XSIP

SIPneo3 Automatically sanitises the floor-standing, tank fed POU or bottled 3300XSIP cooler overnight, every night 24/7

How SIPneo3 Self-Sanitising System works

- SIPneo3 is a programmable ozone generator. The resulting hygiene level protects your customers health, whilst SIP sleep mode reduces their electricity bill
- SIPneo3 Automatically sanitises the floor-standing, tank fed POU or bottled 3300XSIP cooler overnight, every night 24/7
- Eliminates half of your sanitisation call outs
- By activating SIP12-hour sleep mode from 18.00 to 06.00 plus sleep mode on weekends, your customer can make significant savings in electricity
- A hot & cold cooler without sleep mode would use 983KWH per year. With sleep mode this reduces to 377KWH, a saving of 61% at 14p per KWH which would equate to a saving of £85 per year! The saving for an ambient & chilled cooler, using the same formula saves 56% amounting to £11 per year

AA
FIRST
WATER COOLERS
& BOILERS



refreshingly different

3300XSIP Legendary Reliability


Avoids Hand Contact With Push Paddle Taps
& SIPneo3 Automatic Sanitisation

Accessories For The 3300X

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



Filter housing with carbon block candle & nanofilter



10 litre overflow system with alarm to signal when full. (Factory fitted)



Cowling to fix the cooler securely to the wall. (Supplied separately)



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)



SIPneo3 overnight self-sanitising system can be purchased as an accessory for self-installation into your tank-fed pou or bottled cooler



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



Description	Dimensions H x W x D mm	Weight
POU floor standing	1135 x 340 x 340	18
Bottled floor standing	1165 x 340 x 340	18
POU table top	460 x 340 x 340	15
Bottled table top	463 x 340 x 340	15

AAFIRST
WATER COOLERS
& BOILERS

www.aafirst.co.uk