

Accessories

Filter Housing With Carbon Block Candle & Nanofilter.



Installation Rail With Filter. Includes Compression Fitting, 1-Micron Green Filter, Water Block, Copper Pressure Reducing Valve & Non-Return Valve.



The UC800CL Undersink Chiller With Contactless Tap

undersink chiller with contactless swan neck tap to avoid hand to tap contamination

- The Infra Red Sensor is activated by a hand hovering over the Infra Red Sensor at a distance of 2cm to 5cm
- The Sensor is connected to an Inlet Solenoid valve which opens the water supply when activated, and stops the water flowing when the hand is removed
- The Solenoid Valve is powered by two 3V batteries with a tested life span of 86.000 Solenoid activations
- The UC800CL has a cold water capacity of 5 ltr/h with an instant draw off of 1.5ltr below 10°C, from an influent temperature of 26°C. Fan assisted cooling and with an integral pressure arrestor to release pressure build up in the chilling unit. Must be installed in a well ventilated area, to avoid malfunctioning
- The Contactless tap is programmed to stop dispensing after 6 seconds. If that is insufficient to fill your glass or bottle, place your hand again over the sensor to continue dispensing

Description	Dimensions H X W X D (MM)	Dispensing Height	Weight (Kg)
UC800C	290 (+300 WITH TAP) x 410 x 210	20cm	12.5
UC800CL	290 (+300 WITH TAP) x 410 x 210	23cm	12.5

