

Aquality

Refresh, Revive, Rehydrate

High output floor standing POU or bottled cooler from Cosmetal. The Aquality dispenses up to 28ltr/h of chilled and sparkling water and all models feature an integrated cup dispenser for added convenience. The Aquality also has a discreet side panel where the drip tray overflow is stored.

- 25cm (bottled) or 27cm (POU) dispense height.
- Dispenses ambient water + up to 28ltrs/h chilled & 28ltrs/h sparkling water
- High capacity ice bank cooler
- Sturdy and robust build by Cosmetal

Accessories

Installation Rail & Filter

Includes compression fitting, 1-micron green filter, water block, copper pressure reducing valve & non-return valve.



Klaran UVC LED

Protects direct chill water coolers from bacteria, viruses & other pathogens providing point of dispense protection. Available as factory fitted or for self installation.



Drip Tray Overflow

We offer a purpose built Aquality drip tray overflow container. Features an alarm that sounds when full and stores 3ltrs of waste water before needing to be emptied.



Gas & Regulator

Carbonated coolers require a gas regulator to connect the CO² cylinder. Our REGCO2 gas regulator is suitable for 600gm disposable CO² cylinders.



Description	Code	Hourly Output Capacity	Dispense Height	Dimensions H x W x D (mm)	Approx. Weight
POU Ambient & Chilled	CEAQ20P	Ambient + 20ltrs/h Chilled	27cm	1180 x 345 x 337	20kg
Bottled Ambient, Chilled & Sparkling	CEAQ22BWG	22ltrs/h Chilled & Sparkling	25cm	1180 x 345 x 337	20kg
POU Ambient, Chilled & Sparkling	CEAQ28PWG	28ltrs/h Chilled & Sparkling	27cm	1180 x 345 x 337	20kg